



MP15

Single direction Vibratory Plates



This plate proves that performance is valuable

This Wacker Neuson vibratory plate offers functionality and performance at a real value price. The compact design allows for compaction of mixed soils in the narrowest of spaces – even in extremely narrow trenches. The guide handle with vibration damping means longer working hours and less fatigue for the operator.

- This plate is optimally suited for a variety of compaction applications thanks to its high speed and simple maneuverability.
- Specially designed exciter bearings reduce maintenance and are suitable for hot asphalt applications.
- Ergonomically designed lifting handles make loading and unloading from transport vehicles easier for the operator.
- A rugged water tank comes as standard, and leads to higher operator comfort and improved productivity during any asphalt works.
- A wheel kit is optionally available as accessory.

MP15 Standard Package includes operator's manual and parts book.

Item No. 0630131

For easier transportation a wheel kit is optionally available as accessory. Accessory no. 300_5300404314100001

Technical specifications

Operating data

| | |
|----------------------------------------------|-----------------------|
| Operating weight (without water/fuel) | 82 kg |
| Centrifugal force | 15 kN |
| Base plate size (w × l) | 500 × 588 mm |
| Advance travel max. (depending on soil) | 20 m/min |
| Advance travel max. (depending on asphalt) | 23 m/min |
| Surface capacity max. (depending on soil) | 615 m ² /h |
| Surface capacity max. (depending on asphalt) | 686 m ² /h |

Engine / Motor

| | |
|---------------------|------------------------------------------------------|
| Engine / Motor type | Air-cooled, single cylinder, 4-cycle gasoline engine |
|---------------------|------------------------------------------------------|



**WACKER
NEUSON**
all it takes!

| | |
|-------------------------------------|---------------------|
| Engine / Motor manufacturer | Wacker Neuson |
| Engine / Motor | WN6 |
| Displacement | 179 cm ³ |
| Engine performance (max.) at rpm | 4.2 kW 3,600 rpm |
| Fuel consumption | 1.5 l/h |
| Tank capacity (water) | 8.3 l |
| Tank capacity (fuel) | 3.6 l |

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2016 Wacker Neuson SE.